

# Service Bulletin



Information for  Service Mgr.  Shop Foreman  Parts Mgr.  Mechanics

Nov. 5, 1958

No. 58-84

TO ALL CHRYSLER AND IMPERIAL DEALERS:

This bulletin is to supplement the information contained in Chrysler Service Bulletin No. 58-24, dated January 6, 1958.

The 1958 Chrysler C-300D distributor advance specifications for the Auto-Lite No. IBS-4007 Distributor are as follows:

MISCEL-  
LANEOUS

Centrifugal (governor) Advance  
 (Distributor r.p.m. and Degrees)

No Advance	300-400 r.p.m.	0°
Start	400 r.p.m.	0° - 4°
Intermediate	450 r.p.m.	2° - 5°
Maximum	1050 r.p.m.	5.5° - 7.5°

300-D  
 DISTRIBUTOR  
 ADVANCE

Vacuum Advance  
 (Distributor Degrees)

Start	7.5" to 8.5" Hg.	0°
Intermediate	12" Hg.	5.5° - 7.5°
Maximum	16" Hg.	10° - 12°

SPECIFICA-  
TIONS

CHRYSLER

Please refer to this bulletin when servicing a 1958 Chrysler 300D distributor and attach this bulletin to Service Bulletin No. 58-24 when placing in file.

ALL 1958  
300-D

MODELS

*C. T. McClure*

C. T. McCLURE  
 Director of Service

11007